SUNWARD

Excavator SWE 330B

Operating Weight	**33.2t**
Engine Power	**202kW/2000rpm**
Engine Brand	**ISUZU**
Standard Bucket Capacity	**1.5m³**
Max. Digging Depth	**7.485m**



Excavator SWE330B

Parameter

ENGINE	
Brand	ISUZU
Model	AH-6HK1X-S
Type	6-cylinder 4-stroke water cooled
Displacement	7.79L
Power	202kW/2000rpm

DIMENSIONS	
Counterweight Clearance	1195mm
Tail Swing Radius	3390mm
Shipping Length	11175mm
Shipping Width	3190mm
Cab Height	3120mm

ELECTRIC SYSTEM	
Nominal Voltage	24V
Batteries	120Ah
Alternator	24V-50A
Starter	24V-5kW

WORKING RANGES	
Max. Cutting Height	10665mm
Max. Loading Height	7465mm
Max. Digging Depth	7440mm
Max. Vertical Wall Digging Depth	6820mm
Max. Digging Reach	11330mm
Max. Digging Reach (Ground)	11130mm
Bucket Digging Force	240kN
Stick Digging Force	177kN
Ground Pressure	61kPa
Swing Speed	10.3rpm

DRIVE	
Max.Travel Speed (2nd/1st)	4.8/3.2 km/h
Gradeability	35°
Max. Traction	279kN


CAPACITY	
Fuel Tank	650L
Hydraulic Oil Tank	290L


UNDERCARRIAGE	
Undercarriage Width	3190mm
Track Height	1070mm
Tumbler Distance	4030mm
Track Length	4945mm
Shoe Width	600mm


HYDRAULIC SYSTEM	
Main Pumps	
Type	2 piston pumps
Displacement	268 L/min
Working Pressure	31.4/34.3 MPa

Excavator
SWE 330B

Working Ranges







Load Capacity

X(m) / Y(m)	2m		3m		4m		5m		6m		7m		8m					
	Front(kg)	Side(kg)	Front(kg)	Side(kg)	Front(kg)	Side(kg)	Front(kg)	Side(kg)	Front(kg)	Side(kg)	Front(kg)	Side(kg)	Front(kg)	Side(kg)	Front(kg)	Side(kg)	Front(kg)	Side(kg)
8.0	-	-	-	-	-	-	-	-	-	-	*7540	6730	-	-	-	-	*4750	*4750
7.0	-	-	-	-	-	-	-	-	-	-	*7560	6750	*6350	5120	-	-	*4580	*4580
6.0	-	-	-	-	-	-	-	-	-	-	*7930	6660	*7680	5120	-	-	*4490	*4490
5.0	-	-	-	-	-	-	-	-	*9310	8540	*8530	6490	*8020	5040	*6030	3920	*4500	3740
4.0	-	-	-	-	*15770	*15770	*12380	11060	*10480	8170	*9280	6270	7940	4910	6370	3870	*4580	3470
3.0	-	-	-	-	*19190	14680	*14330	10400	*11710	7780	9790	6030	7770	4760	6280	3780	*4750	3300
2.0	-	-	-	-	*11750	*11750	*16010	9820	12340	7420	9530	5790	7600	4600	6190	3690	*4990	3210
1.0	-	-	-	-	*11220	*11220	16360	9410	12000	7130	9300	5590	7480	4470	6100	3610	*5340	3200
0.0	-	-	-	-	*13550	13060	16070	9170	11770	6930	9140	5440	7340	4360	6030	3550	5610	3280
-1.0	-	-	*10200	*10200	*17350	13050	15940	9060	11640	6810	9030	5340	7270	4300	6000	3520	5890	3450
-2.0	*11520	*11520	*14910	*14910	*21820	13130	15940	9050	11600	6780	9000	5310	7260	4290	-	-	6360	3750
-3.0	*16100	*16100	*20250	*20250	*20570	13300	16030	9130	11650	6820	9040	5350	7320	4350	-	-	7130	4240
-4.0	*21320	*23240	*23240	*23240	*18690	13560	*15310	9300	11790	6950	9180	5470			-	-	8420	5040
-5.0	-	-	*19490	*19490	*15880	13930	*13010	9580	*10410	7200					-	-	*9190	6510

Notes:

1) Load with * is limited by hydraulic capacity and based on ISO 10567. Rated loads do not exceed 87% of hydraulic capacity.

2) Load without * is limited by tipping load and based on ISO 10567. Rated loads do not exceed 75% of tipping load.

SUNWARD INTELLIGENT EQUIPMENT CO.,LTD
Add: Sunward Intelligent Industrial Park, Xingsha, Changsha, 410100, China
Tel: 0086-731 8357 2828
Fax: 0086-731-8357 2661
Web: http://www.sunward.com.cn
E-mail: international@sunward.com.cn; info@sunward.cc
P.C: 410100